

Full Line Of Tire Changers

FOR ALL OF TODAY'S VEHICLES... AND TOMORROW'S



626THP Tilt Tower

- Elite pneumatic tilt tower tire changer comes standard with the Accu-Pro Mounting Helper to clamp up to 26" outside.
- Heavy tower and cabinet for maximum rigidity saves wheels from damage by eliminating tower flex.
- The Accu-Pro's 3-point positioning makes mounting lowprofile, PAX and run-flat tires effortless.
- High-performance mount/demount head with tire iron slot provides an extra pressure point for added versatility.
- Proven to withstand the high demands of a high volume tire shop.
- Tested and PAX approved. Optional PAX Adapter, part #SM102666.




Adjustable 3-position bead-breaker to accommodate large wheel diameters with a telescopic adjustment to increase width capability.



Unique telescoping tower allows for wide rims and produces added strength.



Optional jaw protector covers, part #SM103394 lock into place for extra safety. Protector covers prevent accidental rim damage.



Non-opposing adjustable jaws with embossed dimensions for easy, fast and accurate clamping.



Safety Inflation System secures rim during inflation to prevent operator injury and decrease shop liability.

526THP Tilt Tower

- High-end tire changer with manual tilt tower provides outside clamping up to 26".
- Heavy tower and cabinet for maximum rigidity saves wheels from damage by eliminating tower flex.
- Non-opposing jaws with embossed dimension makes clamping faster and more accurate.
- Accu-Pro Mounting Helper Assembly assists in mounting and demounting low-profile and run-flat tires.
- High-performance mount/demount head with tire iron slot designed for low profile tires.
- Three-position bead-breaker with telescoping adjustments increase depth and width bead-breaking capacity.
- Inflation jets, built into clamps, ensure correct positioning for easy bead setting.
- PAX capable with optional PAX adapter kit, part #SM102666.



Accu-Pro Pneumatic Mounting System (HP)

Avoid rim damage - no metal contact with rim.

Integrated rollers and bead depressor designed to apply pressure in the right places to keep the top bead in the drop center, preventing accidental reseating.

Hands-Free - Mount the most difficult highperformance low-profile tires with ease. Changing low-profile, run-flats and PAX tires only requires one technician.



Accu-Pro Mounting Helper shown easily mounting the top bead on 26" rim.



Locking roller disc lifts and removes bottom bead effortlessly and securely.

Swing Arm Tire Changers



326SFA & 326S

- 26" Outside clamping capacity standard.
- Three-position adjustable bead-breaker accommodates large wheels and tires.
- Designed to provide maximum rigidity and torque.
- High-performance mount/demount head with tire iron slot designed for low-profile tires.
- Features adjustable non-opposing jaws with inflation jets.
- Following Arm (FA) assist applies additional pressure points to easily mount difficult tire.

Model 326S is available without the Following Arm (FA).





320S

- Classic swing arm design for outside clamping capacity up to 21".
- Three position bead-breaker arm to accommodate large wheels and tires.
- High-performance mount/demount head with tire iron slot designed for low profile tires.
- Non-opposing jaws with inflation jets.
- Avoid injury with the standard Safety Restraint Inflation System.

Speciality Tire Changers

220A

- \bullet Articulating arm design with 21" outside clamping capability.
- Uniquely designed for independent automotive shops.
- Adjustable bead-breaker to accommodate up to 16" wide tires.
- Plastic mount/demount head for extra wheel protection.
- Optional plastic jaw covers available, part # SM101402.
- Standard Safety Inflation System secures rim during inflation.



High-performance mount/demount head _ with tire iron slot designed to provide extra assistance and increase versatility.

The optional Bead Depressor Tool, part #SM103261 assists in mounting lowprofile tires



Heavy Duty Tire Changers

Accu-turn Heavy-Duty Tire Changers Standard Features:

- Single piece heavy steel frame construction.
- Bi-directional chuck offers two rotation speeds.
- Low-voltage movable remote control for added safety and versatility.
- Hydraulic gearbox with pressure regulating valve.
- Four-jaw universal chuck lifts and operates in vertical position. (Models 452HD and 426HD).

460HD

The ideal tire changer for handling farm wheels, over-the-road wheels, as well as earth moving and industrial wheels ranging from 14" to 60". Features a six-jaw universal chuck for stronger and more secure clamping. Unique telescoping mounting device for extra ease.

452HD

This versatile tire changer is capable of handling a large range of wheels ranging from 14" to 56" including rims with wells, tubeless rims or rims with a ring.



426HD

Well-suited to accommodate truck and bus wheels from $14^{\prime\prime}$ to $26^{\prime\prime}$, including tubeless rim or tire with rings.





	460HD	452HD	426HD	
Inside Clamping	14-60"	14-56"	14-26"	
Rim/Tire Width	61"	35"	31.5"	
Tire Diameter	114″	90.5"	64.5"	
HP Motor	1	1	1	
Electric Requirements	220V, 3PH	220V, 3PH	220V, 3PH	
Weight	3750	1945	1310	
Width	114″	82"	64"	
Depth	105″	69"	55″	
Height	82"	69"	49"	

Specifications and Features

	220A	320S	326\$	326SFA	526T	526THP	626THP
Inside Clamping	12-23"	12-23"	12-28"	12-28"	12-28"	12-28"	12-28"
Outside Clamping	10-21"	10-21"	10-26"	10-26"	10-26"	10-26"	10-26"
Rim/Tire Width	12"	12"	12"	12"	15"	15"	16"
Rim Width	13"	15"	15"	15"	15"	15"	15"
Tire Diameter	46"	40"	44"	44"	40"	40"	40"
Bead-Breaker Capacity	16"	16"	18"	18"	18"	18"	18"
Air Pressure	100-170 lbs	100-170 lbs	100-170 lbs	100-170 lbs	100-170 lbs	100-170 lbs	100-170 lbs
HP Motor	1	1	1	1	1	1	1
Electric Requirement	120v 20 A	120v 20 A	120v 20 A	120v 20 A	120v 20 A	120v 20 A	120v 20 A
Weight	451 lbs	500 lbs	500 lbs	550 lbs	500 lbs	750 lbs	900 lbs
Width	30"	30"	30"	30"	30"	30"	30"
Depth	44 ½"	37 ½"	37 ½"	37 ½"	37 ½"	37 ½"	37 ½"
Height	70"	68"	74"	74"	72"	72"	72"
Articulating Arm	Χ						
Swing Arm		χ	Χ	Х			
Tilt Tower					χ	χ	χ
Dual Cylinder Mnt Helper (Accu-Pro)						χ	χ
Telescoping Tower							χ
Telescoping Bead-Breaker	Х	χ	Χ	Х	Χ	χ	χ
3-Position Bead-Breaker		χ	χ	χ	Χ	χ	χ
Non-opposing Jaws	Х	Х	Х	Х	Х	Х	χ
Adjustable Jaws			χ	χ	χ	χ	χ
Inflation Jets Move With Jaws		Х	Х	Х	Х	Х	χ
Slotted Mount Head For Low-Profile Tires	χ	χ	χ	Х	χ	χ	X
Safety Restraint Inflation System	Х	Х	Х	Х	Х	Х	Х
Powder Coat Finish	χ	χ	χ	Χ	χ	χ	χ
5-Year Transmission Warranty	Х	Х	Х	Х	Х	Х	Х





SM102666

PAX Tire Kit for use with Accu-Pro Mounting Helper (includes roller, rim protectors, bead levers, and center post adaptors).



SM102529

Plastic duck head kit (requires 102765 adapter for all models except 220A).



SM103076

Set of four 26" turntable clamp adapters for models 220A and 320S.



SM101402

Plastic clamping jaw protectors for models 220A and 320S. Use **SM103394** for models 326S/SFA, 526T/THP, and 626THP.



SM102090

Bead breaker plastic protection kit (includes SM101800 and SM102088).



SM102711 Inflation system kit.



SM103261

Zeppa bead depressor tool for standard drop center rims. Use SM103216 Zeppa bead depressor tool for deep drop center rims (more than 2").



SM102725

Plastic protection for back side of mount/demount heads.



SM101608
Mount/demount head protective plastic inserts



SM102014

Set of four 8" wheel clamp adapters for 8" wheels on models 220A and 320S. Use **SM103286** for models 326S/SFA, 526T/THP, and 626THP.



SM102724

Set of four motorcycle clamp adapters for use on models 220A and 320S. Use SM103284 for models 326S/SFA, 526T/THP, and 626THP.



SM103302

Bead depressor tool, adjustable plastic clamp style.

Accu Offers a Complete Line of Wheel Service Equipment



Product Information www.AccuTurn.com



Accu Industries, Inc.

Headquarters: P.O. Box 15540 Richmond, VA 23227 11126 Air Park Road Ashland, VA 23005 Product and Sales Information Accu Products Warehouse www.AccuTurn.com 804-798-4900 / 804-365-7959 9:00am-4:00pm EDT